

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
14 June 2001 (14.06.2001)


PCT

(10) International Publication Number  
**WO 01/41546 A2**

- (51) International Patent Classification: Not classified (72) Inventors: BRUMITT, Barrett; 4010 266th Avenue NE, Redmond, WA 98053 (US). SHAFER, Steven; 1314 Fifth Ave. West, Seattle, WA 98119 (US). MEYERS, Brian; 4040 W. Lk. Sam Pky SE, Bellevue, WA 98008 (US).
- (21) International Application Number: PCT/US00/32082
- (22) International Filing Date: 21 November 2000 (21.11.2000) (74) Agents: WATSON, Mark et al.; Lyon, Harr, & DeFrank, 300 Esplanade Drive, Suite 800, Oxnard, CA 93030 (US).
- (25) Filing Language: English (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (26) Publication Language: English
- (30) Priority Data:  
60/170,285 10 December 1999 (10.12.1999) US  
09/657,871 8 September 2000 (08.09.2000) US
- (71) Applicant: MICROSOFT CORPORATION [US/US]; Patent Group, One Microsoft Way, Redmond, WA 98052 (US). (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

[Continued on next page]

(54) Title: GEOMETRIC MODEL DATABASE FOR USE IN UBIQUITOUS COMPUTING



(57) Abstract: A system and process for providing a geometric model database for use in a ubiquitous computing environment. In general, the geometric model database system and process is capable of accepting information about the geometric state of the environment (200), building a geometric model of this environment (202), maintaining and storing the geometric model (204), and handling queries about the environment's geometric state (206). The task of building a geometric model begins by establishing a set of entities that are of interest in the environment (300). An entity represents an object which exists in the physical world. In the geometric model database, an entity is represented by a coordinate frame and an extent (302). Extents refer to the physical size, or some service region such as a field of view, associated with an entity. The location of an entity in the physical world is defined using "measurements" (304). In general, a measurement is simply a mathematical description of the geometric relationship between two entities. More precisely, a measurement describes the position and orientation of one entity's coordinate frame, expressed in terms of another entity's coordinate frame. Measurements originating at an entity's frame are expressed in terms of that frame. While various mathematical representations of the geometric relationship between entities could be employed, a preferred one characterizes a measurement as the relative position, and the relative orientation or heading, of two entities along with a covariance matrix which describes the uncertainty in these values.

WO 01/41546 A2



patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *Without international search report and to be republished upon receipt of that report.*

**GEOMETRIC MODEL DATABASE FOR USE IN UBIQUITOUS COMPUTING****BACKGROUND OF THE INVENTION**

5

**Technical Field:**

The invention is related to a ubiquitous computing environment, and more particularly to a system and process for providing a geometric model database for use in aggregating information and responding to queries about the environment's geometric state.

**Background Art:**

Ubiquitous computing revolves around extending computational activities beyond the current desktop model and into the environment. In future homes and offices, access to computing should be as natural as access to lighting. Users should not be required to go to a special place (i.e., the desktop) to interact with the computer. Rather, the computer should be available to interface with the user anywhere in the home or office (or more generally anywhere in an arbitrarily large environment), through whatever set of devices is available, be they fixed or carried by the user.

It is noted that the term computer is used loosely here in that the user actually would have access to a wide variety of computing and information services, which will likely employ many computers and "smart" devices such as PDA's, mobile phones, cameras, etc. For example, computing services such as web browsing, document editing, or video conferencing are envisioned. Thus, it should be understood that when the term computer is used in connection with the concept of ubiquitous computing, in actuality many computers may be involved non-exclusively in a single interactive session.

The usefulness of a ubiquitous computing system is greatly enhanced if it maintains an awareness of the users, including such things as their locations and

orientation (i.e. which way they are facing). One goal of such a system would then be to understand the physical and functional relationship between the users and various I/O devices. Such knowledge could be employed to allow a user to move from room to room while still maintaining an interactive session with the computer.

- 5 Through cameras, microphones and other perceptual devices or sensors, the user would always be in touch with the computer, no matter where the computer is physically located. Conversely, through displays, speakers, and other output devices, the computer will always be able to contact the user. For example, the system could track the location of a person and transfer a current computing session
- 10 from a monitor in one room, to a different monitor in another room where the user enters, while the user continues to control the session via a PDA carried on his person.

- As can be imagined, a fundamental unifying aspect of ubiquitous computing is
- 15 a representation of the physical relationships between people, things, and devices – in other words a geometric model of the environment. To date, no satisfactory geometric modeling program exists.

- The present invention provides this needed geometric modeling program in
- 20 the form of a dynamic database that maintains information about the physical relationships between users, various I/O devices and sensors, as well as passive things in the world such as furniture, doors and walls.

- It is noted that in the remainder of this specification, the description refers to
- 25 various individual publications identified by a numeric designator contained within a pair of brackets. For example, such a reference may be identified by reciting, "reference [1]" or simply "[1]". Multiple references will be identified by a pair of brackets containing more than one designator, for example, [3, 18, 22, 9]. A listing of the publications corresponding to each designator can be found at the end of the
- 30 Detailed Description section.

**DISCLOSURE OF THE INVENTION**

The present invention is directed toward a system and process for providing a geometric model database for use in a ubiquitous computing environment. In general, the geometric model database system and process is capable of accepting information about the geometric state of the environment, building a geometric model of this environment, maintaining and storing the geometric model, and handling queries about the environment's geometric state.

The task of building a geometric model begins by establishing a set of entities that are of interest in the environment. An entity represents an object which exists in the physical world (e.g., a person, I/O device, or sensor). In the geometric model, an entity is represented by a coordinate frame (or just "frame" for short) and an extent. The frame of an entity has a pre-selected origin somewhere on or within the object. Coordinate axes extend from this origin. In a preferred embodiment of the model, only the orthogonal x and y axes are used and represent the axes that could be "seen" looking down onto the environment. Entity identification information is provided to the geometric model program from external programs. When an entity is first identified, the geometric model program assigns an entity identifier (ID) that uniquely identifies the entity. This information is provided back to the outside program which introduced the entity, and possibly to some other repository of identification information. The entity ID is used by outside programs when updating information about an entity or when making a query about the physical relationships between entities. Entities may be created or deleted and any time during the period which the model exists.

The location of an entity in the physical world is defined using "measurements". In general, a measurement is simply a mathematical description of the geometric relationship between two entities. More precisely, a measurement describes the position and orientation of one entity's coordinate frame, expressed in terms of another entity's coordinate frame. Measurements originating at an entity's frame are expressed in terms of that frame. In addition, measurements ending at an entity's frame, end at the origin of that frame. While various mathematical

representations of the geometric relationship between entities could be employed, a preferred one characterizes a measurement as the relative position, and the relative orientation or heading, of two entities.

- 5           A way to envision the foregoing method of representing the locations of the entities is to imagine that the frames of the entities are related by a chain of measurements. Sensors in the environment provide each link in the measurement chain. However, the sensor readings are processed outside the geometric model program and just the relative coordinates are provided as measurements to the
- 10   model program. As with the entities, a measurement ID is assigned by the geometric model program to each new measurement provided to it. These measurement IDs are issued back to the program providing the measurement (and possibly to some outside database) so that any updates that are provided in the future can be identified as being associated with the previous measurement.
- 15   Typically, a new measurement is used to replace the existing measurement with that ID.

- Measurements in the geometric model preferably also reflect the spatial uncertainty associated with the method used to obtain them. One way of introducing
- 20   an uncertainty estimate into the measurements is to employ a Gaussian uncertainty model where rather than a measurement being a particular value, it is provided to the geometric model program as a mean estimate for each coordinate and a covariance matrix for each that is indicative of the uncertainty of the coordinate mean. One advantage of characterizing the measurements in the foregoing way is
- 25   that it can be used to enhance certain optional procedures performed within the geometric model program that are designed to test the accuracy and revise the measurements provided to the program. One class of these methods employs the concept of cycle-based constraints. A cycle is a loop formed by connected entities frames. In the environment these loops represent measurements from a first entity
- 30   frame (which could be any one in the loop) to the next and so on until a measurement connects the next to last entity frame back to the first entity frame. The significance of a cycle is that the measurements around the loop should return precisely to where they started, i.e. a "zero difference". If they do not then the

previously provided uncertainty estimates could be used to adjust the measurements within the loop to obtain the desired zero difference. In this case, measurements are adjusted in proportion to the amount of uncertainty in each one. Specifically, the measurement cycles existing in the geometric model are identified. One of the entities making up each cycle, for which an actual location corresponding the origin of its frame is known, is selected as the first entity of the cycle. The difference between the actual location of the first entity frame's origin and the location of that origin as indicated by following the chain of measurements making up the cycle is then determined. Revised measurements for the identified cycles are computed next by simultaneously adjusting the measurements of all the identified cycles based on their associated uncertainty estimates, so as to make the difference between the actual location of the first entity frame's origin in each of the identified cycles match the location of that origin as indicated by following the chain of measurements making up the cycle.

It is further noted that there may be more than one measurement input from different sources to describe the geometric relationship between the same two entity frames. Each of the measurements would be assigned a different ID and so could co-exist in the same model. Thus there would be a question as to which measurement to use in responding to a query. One way to deal with this situation is to simply chose one of them arbitrarily for use in responding to a query, as was done in tested embodiment of the geometric model program. Another way would be to choose the measurement with the lowest uncertainty estimate. Alternatively, the two measurements could be combined using the relative uncertainties as weights in the combination process [1].

Another accuracy testing procedure that could be implemented based on the aforementioned cycles involves detecting inconsistencies. This would entail following the measurements forming a cycle around from a first entity frame to compute a location of the origin of the first frame, while using the uncertainty estimates associated with each measurement to compute an uncertainty region around the computed origin location. The first entity frame can be any one in the loop for which an actual location corresponding the origin of the frame has been

previously specified, and the uncertainty region essentially defines a area around the computed location. If the specified location of the entity frame chosen as the first in the cycle falls within the uncertainty region, then the measurements are considered to be accurate. If, however, the specified location falls outside the aforementioned  
5 region, then it can be surmised that at least one of the measurements making up the cycle is incorrect. It would not be known which measurement or measurements in the cycle are incorrect. However, knowing that at least one of them is in error, the geometric model program could be designed to disregard all the measurements that are part of the cycle. Further, the geometric model program could provide feedback  
10 to the program or programs that inputted the suspect measurements and request that new measurements be provided. The inconsistency check would then be performed using the updated measurements.

The foregoing accuracy testing procedures can also be combined as follows.  
15 First, all the cycles of measurements existing in the geometric model are identified. Then, for each identified cycle, the previously-described process for detecting inconsistencies in the measurements of a cycle is performed. If it is determined that at least one of the measurements making up the cycle is inconsistent, then the measurements are ignored and potentially replaced. However, if the computed  
20 location of the first entity frame of the cycle is not exactly the same as the specified location but falls within the aforementioned uncertainty region, then revised measurements for the cycle are computed by simultaneously adjusting the measurements based on their associated uncertainty estimates so as to make the difference in the actual location of the first entity frame's origin in each of the  
25 identified cycles match the location of that origin as indicated by following the chain of measurements making up the cycle.

It is also noted that any of the foregoing accuracy testing methods could be repeated each time a new or updated measurement is received. Or, alternately, the  
30 methods could be repeated on a periodic basis.

It was mentioned previously that an entity is represented in the geometric model as a coordinate frame and an extent. Real world entities will have some



physical size. In addition, a physical object could have some service region, such as a field of view associated with a camera or display device. It is advantageous to augment the geometric model with these region descriptions, which are called extents. Thus, an inputting program would include in its description of an entity any  
5 extents associated with the entity. The geometric program would preferably treat each entity-extent combination as separate entities with a measurement of zero between them. Thus, each entity has only one extent, but multiple entities may refer to the same physical device. By default in the preferred embodiment, if no extent is explicitly specified for an entity, a point extent is assumed. This point extent can be  
10 defined as being located at the origin of the entity's frame, or at a location having some prescribed geometric relationship to the origin of the entity's frame. It is noted that the description of the area in the environment associated with an extent is expressed in terms of the coordinate frame of the corresponding entity. The extent of an entity can be expressed as having any planar geometric shape. However, in  
15 tested embodiments of the geometric model program the area associated with an extent was expressed as a polygon, (including degenerate cases such as a point when no extent is specified or a line segment such as in the case of a flat display screen which appears as a line from above).

20 The geometric model of the environment is constructed from three components input by outside programs. Namely, entities, extents associated with entities, and measurements between entity frames. However, the environment being modeled will typically change. Thus, it is necessary that the presence of an entity and the measurements between entity frames be updated on an on-going basis to  
25 keep the geometric model current. The aforementioned entity and measurement IDs are used in this updating process. In view of the need to keep the geometric model current an assumption is made that some mechanism is in place which causes the outside programs feeding the model program to input changes. As indicated previously, when an entity is created, an entity ID is assigned. Thus, any new entity  
30 introduced by an outside program would also be issued a unique entity ID. Whenever, a outside program refers to an entity it does so by using the assigned entity ID. As a consequence, the outside programs must have the capability to retain these IDs. If an outside program indicates that an entity is no longer in the

environment, the entity ID is deactivated and preferably not used again to prevent confusion. In a similar way, outside programs that input updated measurements would do so by referring to the appropriate measurement ID. The same measurement ID can be retained for the updated version as the ID refers to the existence of geometric relationship between two entities not a specific instance of that relationship. However, if an entity associated with a measurement is eliminated from the geometric model, all the measurements which refer to that entity should also be deleted, and preferably the measurement ID retired to prevent confusion.

The geometric model database is preferably stored in a readily accessible memory, such as a RAM, while the geometric model program is running so as to facilitate updating the model and processing queries concerning the geographic relationships represented by the model. However, when the program is exited the model may be lost. Of course, the geometric model database could be rebuilt each time the program is executed. However, this requires the outside programs that feed entity, measurement and extent information into the geometric model program to supply this information each time. While a typical ubiquitous computing environment is dynamic in nature, many things do not change that often, such as the location of many I/O devices and sensors. Thus, there is some redundancy in re-building the model each time the geometric model program is executed that could be avoided. One way of avoiding this redundancy would be to store the relatively fixed or static portions of the model in a non-volatile memory and initialize the model using this information each time the geometric model program is executed. It is noted however, that since the entity IDs and measurement IDs associated with the static model data would be retained from one session to the next, any outside program that wishes to provide inputs or make queries would have to have the capability of permanently storing this information, or perhaps more practically, obtaining the IDs from a separate database maintained for that purpose.

In the event that some of the fixed portions of the geometric model change, or new fixed entities, etc., are added to the model, the initializing database could be updated accordingly so as to be as accurate as possible the next time the geometric model program is executed.

The primary purpose of creating and maintaining the geometric model of the ubiquitous computing environment is to respond to queries about the geometric relationships between entities. While a query could be as simple as what extent is associated with a particular entity, typically the requested information will be directed at the relationships between the various entities and/or their extents. There are two fundamental types of queries about these relationships that the geometric model program will be called upon to answer. The first type is a query concerning the relative relationship between two entities. There may be a single measurement already existing between the frames of the entities in question. If so, the answer to the query is straightforward. However, suppose there is no direct measurement between the between entities involved in the query. If at least one path of measurements exists between two entity frames, then a single geometric relationship can be derived between them. However, in such a case the geometric relationship must be derived from the multiple measurements making up the path. The first part of this process is to find a measurement path between the two entity frames in question. One way of doing this is to find a path having the fewest number of measurements between the query entities. This can be accomplished using a breadth-first search procedure. It is noted that if two paths have the same number of measurements (i.e., a tie), either could be chosen arbitrarily, or some selection criteria such as the collective uncertainty of the path could be employed to make the choice. The next phase of the response to the first type of query involving the geometric relationship between two entities is to compute a single measurement describing the relationship and output it to the querying program.

The second type of query concerns a request to find an entity or set of entities whose extents have a particular geometric relationship to a given entity. The first phase of this process is to define the relationship between the given entity frame and each of the other entity frames in terms of the given entity's coordinate frame. This is accomplished just as it was in responding to the first type of query, with the exception that it is repeated to find the relationship between the given entity frame and every other entity frame, not just for one other. The next phase in this type of query could generally be characterized as a region intersection problem. Essentially, some region associated with a given entity frame is specified. This region could be a

newly defined region, or it might be the aforementioned extent of the entity. A newly defined region could be any desired planar shape, however, for convenience the following description will assume the newly defined region (or one corresponding to an entity's extent) is a polygon as was used in tested embodiments of the geometric model program. The extents associated with all the other entities would be transformed using the computed relationships into the given entity's coordinate frame. The region intersection technique would then be employed to determine if extents associated with the other entities intersect the defined region. Those entities whose extents are discovered to intersect the region would be reported to the program making the query.

When the purpose for a query is to determine if one entity is in the field of view of another, such as where the querying program wants to display something intended for the person to see, the aforementioned rotational coordinates used to indicate the "heading" of an entity could be used in answering the query. For instance, if the rotation component associated with the person indicates that the display screen would be in his or her field of view, then this would be reported. If not, then it could be reported to the querying program that the person could not see the display screen. The same procedure could be performed in the context of the display screen to ensure that it is oriented such that the person can see it.

It is noted that a query could be of a one-time or "one-shot" nature, or may be a standing query. For a one-time query, the querying program would request the desired geometric information and receive a one-time response. However, a standing query would be one predicated on some event, and every time this event occurred, a response to the query would be provided. For example, the previously discussed query concerning whether a person could clearly see a display screen might be requested to be responded to every time the person of interest is added to the geometric model of the environment (e.g., enters a room). It is also noted that because the environment is dynamic, the response to such a query may have to be re-computed each time it is responded to, rather than relying on the previous response.

In addition to the just described benefits, other advantages of the present invention will become apparent from the detailed description which follows hereinafter when taken in conjunction with the drawing figures which accompany it.

5

### BRIEF DESCRIPTION OF THE DRAWINGS

The specific features, aspects, and advantages of the present invention will become better understood with regard to the following description, appended claims,  
10 and accompanying drawings where:

FIG. 1 is a diagram depicting a general purpose computing device constituting an exemplary system for implementing the present invention.

15 FIG. 2 is a flow chart diagramming an overall process for providing a geometric model database for use in a ubiquitous computing environment to respond to queries about the environment's geometric state in accordance with the present invention.

20 FIG. 3 is a flow chart diagramming a process for building the geometric model database, in accordance with the model building module of the overall process of Fig. 2.

FIG. 4 is a diagram illustrating a preferred measurement scheme employed in  
25 the present invention to describe the location of an entity in the environment, where each measurement describes the position and orientation of one entity's coordinate frame, expressed in terms of another entity's coordinate frame.

FIG. 5 is a diagram illustrating an example of a chain of measurements linking  
30 a series of entities.

FIG. 6 is a flow chart diagramming a first error detection process for identifying and revising measurements that can be used in conjunction with the model building module of the overall process of Fig. 2.

5 FIG. 7 is a flow chart diagramming a second error detection process for identifying and handling errors in measurements that can be used in conjunction with the model building module of the overall process of Fig. 2.

FIG. 8 is a flow chart diagramming a process for responding to queries  
10 concerning the geometric relationship between two entities modeled in the geometric model database, in accordance with the response module of the overall process of Fig. 2.

FIG. 9 is a flow chart diagramming process for responding to queries  
15 concerning a request to find an entity or entities whose extents have a particular geometric relationship to a prescribed region or extent associated with a given entity, in accordance with the response module of the overall process of Fig. 2.

## 20 MODES FOR CARRYING OUT THE INVENTION

In the following description of the preferred embodiments of the present invention, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration specific embodiments in which  
25 the invention may be practiced. It is understood that other embodiments may be utilized and structural changes may be made without departing from the scope of the present invention.

Before providing a description of the preferred embodiments of the present  
30 invention, a brief, general description of a suitable computing environment in which the invention may be implemented will be described. Figure 1 illustrates an example of a suitable computing system environment 100. The computing system environment 100 is only one example of a suitable computing environment and is not

intended to suggest any limitation as to the scope of use or functionality of the invention. Neither should the computing environment 100 be interpreted as having any dependency or requirement relating to any one or combination of components illustrated in the exemplary operating environment 100.

5

The invention is operational with numerous other general purpose or special purpose computing system environments or configurations. Examples of well known computing systems, environments, and/or configurations that may be suitable for use with the invention include, but are not limited to, personal computers, server  
10 computers, hand-held or laptop devices, multiprocessor systems, microprocessor-based systems, set top boxes, programmable consumer electronics, network PCs, minicomputers, mainframe computers, distributed computing environments that include any of the above systems or devices, and the like.

15

The invention may be described in the general context of computer-executable instructions, such as program modules, being executed by a computer. Generally, program modules include routines, programs, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types. The invention may also be practiced in distributed computing environments  
20 where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in both local and remote computer storage media including memory storage devices.

25

With reference to Figure 1, an exemplary system for implementing the invention includes a general purpose computing device in the form of a computer 110. Components of computer 110 may include, but are not limited to, a processing unit 120, a system memory 130, and a system bus 121 that couples various system components including the system memory to the processing unit 120. The system  
30 bus 121 may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. By way of example, and not limitation, such architectures include Industry Standard Architecture (ISA) bus, Micro Channel Architecture (MCA) bus,

Enhanced ISA (EISA) bus, Video Electronics Standards Association (VESA) local bus, and Peripheral Component Interconnect (PCI) bus also known as Mezzanine bus.

5 Computer 110 typically includes a variety of computer readable media.

Computer readable media can be any available media that can be accessed by computer 110 and includes both volatile and nonvolatile media, removable and non-removable media. By way of example, and not limitation, computer readable media may comprise computer storage media and communication media. Computer

10 storage media includes both volatile and nonvolatile, removable and non-removable media implemented in any method or technology for storage of information such as computer readable instructions, data structures, program modules or other data.

Computer storage media includes, but is not limited to, RAM, ROM, EEPROM, flash memory or other memory technology, CD-ROM, digital versatile disks (DVD) or other

15 optical disk storage, magnetic cassettes, magnetic tape, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to store the desired information and which can be accessed by computer 110. Communication media typically embodies computer readable instructions, data structures, program modules or other data in a modulated data signal such as a carrier wave or other

20 transport mechanism and includes any information delivery media. The term "modulated data signal" means a signal that has one or more of its characteristics set or changed in such a manner as to encode information in the signal. By way of example, and not limitation, communication media includes wired media such as a wired network or direct-wired connection, and wireless media such as acoustic, RF, 25 infrared and other wireless media. Combinations of the any of the above should also be included within the scope of computer readable media.

The system memory 130 includes computer storage media in the form of volatile and/or nonvolatile memory such as read only memory (ROM) 131 and 30 random access memory (RAM) 132. A basic input/output system 133 (BIOS), containing the basic routines that help to transfer information between elements within computer 110, such as during start-up, is typically stored in ROM 131. RAM 132 typically contains data and/or program modules that are immediately accessible



to and/or presently being operated on by processing unit 120. By way of example, and not limitation, Figure 1 illustrates operating system 134, application programs 135, other program modules 136, and program data 137.

5           The computer 110 may also include other removable/non-removable, volatile/nonvolatile computer storage media. By way of example only, Figure 1 illustrates a hard disk drive 141 that reads from or writes to non-removable, nonvolatile magnetic media, a magnetic disk drive 151 that reads from or writes to a removable, nonvolatile magnetic disk 152, and an optical disk drive 155 that reads  
10       from or writes to a removable, nonvolatile optical disk 156 such as a CD ROM or other optical media. Other removable/non-removable, volatile/nonvolatile computer storage media that can be used in the exemplary operating environment include, but are not limited to, magnetic tape cassettes, flash memory cards, digital versatile disks, digital video tape, solid state RAM, solid state ROM, and the like. The hard  
15       disk drive 141 is typically connected to the system bus 121 through a non-removable memory interface such as interface 140, and magnetic disk drive 151 and optical disk drive 155 are typically connected to the system bus 121 by a removable memory interface, such as interface 150.

20           The drives and their associated computer storage media discussed above and illustrated in Figure 1, provide storage of computer readable instructions, data structures, program modules and other data for the computer 110. In Figure 1, for example, hard disk drive 141 is illustrated as storing operating system 144, application programs 145, other program modules 146, and program data 147. Note  
25       that these components can either be the same as or different from operating system 134, application programs 135, other program modules 136, and program data 137. Operating system 144, application programs 145, other program modules 146, and program data 147 are given different numbers here to illustrate that, at a minimum, they are different copies. A user may enter commands and information into the  
30       computer 110 through input devices such as a keyboard 162 and pointing device 161, commonly referred to as a mouse, trackball or touch pad. Other input devices (not shown) may include a microphone, joystick, game pad, satellite dish, scanner, or the like. These and other input devices are often connected to the processing unit

120 through a user input interface 160 that is coupled to the system bus 121, but may be connected by other interface and bus structures, such as a parallel port, game port or a universal serial bus (USB). A monitor 191 or other type of display device is also connected to the system bus 121 via an interface, such as a video interface 190. In addition to the monitor, computers may also include other peripheral output devices such as speakers 197 and printer 196, which may be connected through an output peripheral interface 195. Of particular significance to the present invention, a camera 163 (such as a digital/electronic still or video camera, or film/photographic scanner) capable of capturing a sequence of images 164 can also be included as an input device to the personal computer 110. Further, while just one camera is depicted, multiple cameras could be included as input devices to the personal computer 110. The images 164 from the one or more cameras are input into the computer 110 via an appropriate camera interface 165. This interface 165 is connected to the system bus 121, thereby allowing the images to be routed to and stored in the RAM 132, or one of the other data storage devices associated with the computer 110. However, it is noted that image data can be input into the computer 110 from any of the aforementioned computer-readable media as well, without requiring the use of the camera 163.

The computer 110 may operate in a networked environment using logical connections to one or more remote computers, such as a remote computer 180. The remote computer 180 may be a personal computer, a server, a router, a network PC, a peer device or other common network node, and typically includes many or all of the elements described above relative to the computer 110, although only a memory storage device 181 has been illustrated in Figure 1. The logical connections depicted in Figure 1 include a local area network (LAN) 171 and a wide area network (WAN) 173, but may also include other networks. Such networking environments are commonplace in offices, enterprise-wide computer networks, intranets and the Internet.

When used in a LAN networking environment, the computer 110 is connected to the LAN 171 through a network interface or adapter 170. When used in a WAN networking environment, the computer 110 typically includes a modem 172 or other

means for establishing communications over the WAN 173, such as the Internet. The modem 172, which may be internal or external, may be connected to the system bus 121 via the user input interface 160, or other appropriate mechanism. In a networked environment, program modules depicted relative to the computer 110, or portions thereof, may be stored in the remote memory storage device. By way of example, and not limitation, Figure 1 illustrates remote application programs 185 as residing on memory device 181. It will be appreciated that the network connections shown are exemplary and other means of establishing a communications link between the computers may be used.

The exemplary operating environment having now been discussed, the remaining part of this description will be devoted to a discussion of the program modules embodying the aforementioned system and process for providing a geometric model database for use in an ubiquitous computing environment. In general, the geometric model program is accomplished via the following process actions, as shown in the high-level flow diagram of Fig. 2. First, in process action 200, information about the geometric state of the environment is obtained. As will be described in more detail later, this action preferably involves outside programs providing identifying information concerning objects or persons (referred to hereinafter as entities), which are to be included in the geometric model database. In addition, the outside programs would specify the extent of the identified entity and provide measurement information associated with the location of the entity. Both the extent and measurement concepts will be fully described in the sections that follow. A geometric model database of the environment is built based on the information obtained (process action 202), and then queries concerning the geometric relationships between entities in the environment are responded to using the geometric model database (process action 206). In addition, the geometric model database can be maintained by periodically modifying it based on the input of updated information about the geometric state of the environment (process action 204). This updated database is then used to respond to the aforementioned queries. Each of these tasks will be described in detail in the sections that follow.

## 1.0 Building a Geometric Model of The Environment

Referring to Fig. 3, the task of building a geometric model begins by establishing a set of entities that are of interest in the environment (process action 300). An entity represents an object which exists in the physical world (e.g., a person, I/O device, or sensor). In addition, a single physical object may have different components (e.g., a laptop computer with both screen and keyboard sections) that could be included in the geometric model as separate entities. An entity is represented in the geometric model by a coordinate frame (or just "frame" for short) having a pre-selected origin contained on or within the entity, and an extent (process action 302). In a preferred embodiment of the model, only the orthogonal x and y axes are used and represent the axes that could be "seen" looking down onto the environment. For example, the origin of the frame of a display screen might be defined as being in the middle of the screen as viewed from above, with one axis parallel to the screen and one axis perpendicular to the screen. Another example would be a person. A person could be represented in the model by a frame origin coinciding with their center of mass and having one axis pointing in a positive direction to the person's right and the other axis pointing in a positive direction straight ahead of the person. Entity identification information is provided to the geometric model program from "outside" programs. When an entity is first identified, the geometric model program assigns an entity ID that uniquely identifies the entity. This information is provided back to the outside program which introduced the entity, and possibly to some other repository of identification information. The entity ID is used by outside programs when updating information about an entity or when making a query about the physical relationships between entities.

The location of an entity in the physical world is defined using "measurements". In general, a measurement is simply a mathematical description of the geometric relationship between two entities. While various mathematical representations of the geometric relationship between entities could be employed, a preferred one characterizes a measurement as the relative position, and the relative orientation or heading, of two entities. More precisely, a measurement describes the position and orientation of one entity's coordinate frame, expressed in terms of

another entity's coordinate frame. Measurements originating at an entity's frame are expressed in terms of that frame. In addition, measurements ending at an entity's frame, end at the origin of that frame. Any program providing a measurement relating two entities is assumed to know the origin of the coordinate frame of the entities. For example, any program providing measurements which relate the frame of the display screen described above to another frame must be sure that the sensor being used does, in fact, make its measurements relative to center of the screen, or the program must internally transform the measurement so that this is true. Thus, referring to Fig. 3 once again, the next process action 304 performed in building a geometric model is to assign at least one measurement defining the entity's geometric relationship with one or more other entities. This effectively describes its location. Multiple measurements associated with a single entity would occur where separate measurements are supplied between the entity and more than one other entity.

An example of the foregoing measurement scheme is illustrated in Fig. 4. The location of an entity (hereinafter referred to as the destination entity as the measurement ends at the entity), whose frame 402 is shown in the upper right hand corner, in relation to an originating entity (so called as the measurement originates from that entity), whose frame 400 is shown in the lower left hand corner, could be defined by a set of x,y coordinates 404, 406 as viewed from the coordinate frame 400 associated with the originating entity. Specifically, as shown in Fig. 4, the measurement between the frames 400 and 402 of the two entities would include a  $\Delta x$  coordinate 408 associated with the distance between the origins of the two frames along the x-axis 404 of the originating entity's frame 400, and a  $\Delta y$  coordinate 410 associated with the distance between the origins of the two frames along the y-axis 406 of the originating entity's frame 400. The measurement between the frames 400 and 402 of the two entities would also include a  $\Delta \theta$  coordinate 412 associated with the degree of rotation of the destination entity's frame 402 in relation to the originating entity's frame 400. This rotational component is a measure of the relative rotation of the destination entity's frame 402 relative to the originating entity's frame 400 about the axis defined by the positive cross product of the x and y axes 404, 406, assuming a right-handed coordinate system. The rotational component can be

quite useful for entities such as a display screen or a person as it can be used to determine which way the entity is facing. For example, if a display screen were directed away from where a person is facing, the person would not be able to see the screen. Thus just knowing the relative positions of the screen and the person  
5 would not be enough to determine if the person could see the screen. Furthermore, there is no *a priori* reason to expect that all entities have coordinate frames with their X and Y axes aligned. Thus, a rotational component is needed.

A way to envision the foregoing method of representing the locations of the  
10 entities is to imagine that the frames of the entities are related by a chain of measurements. Sensors in the environment provide each link in the measurement graph. However, the raw sensor readings are processed outside the geometric model program and just the relative coordinates are provided as measurements to the model program (along with uncertainty estimates as discussed below). As with  
15 the entities, a measurement ID is assigned by the geometric model program to each new measurement provided to it. These measurement IDs are issued back to the program providing the measurement (and possibly to some outside database) so that any updates that are provided in the future can be identified as being associated with the previous measurement. Typically, a new measurement is used to replace  
20 the existing measurement with that ID. The foregoing chain of measurements model is illustrated in graph of Fig. 5. The lettered vertices 500 in Fig. 5 respectively represent the origin of each entity frame, and the lines 502 connecting the vertices represent the existence of a measurement of the geometric relationship between the connected entities' frames. It is noted that the lines 502 do not imply that the  
25 measurements were taken from (i.e., observed by one of) either of the physical embodiments of either of the pair of connected entities. Rather, they simply represent a relative measurement between the frames of two entities, and may have been derived from a sensor at another location in the environment. It is also noted that the measurements are invertible between two entity frames in the graph. Thus,  
30 a measurement in the graph can represent not only the relative position between entity A's frame and entity B's frame, but also between entity B's frame and entity A's frame.

It is noted that there is a possibility that more than one measurement would be input from different sources to describe the geometric relationship between the same two entity frames. Each of the measurements would be assigned a different ID and so could co-exist in the same model. Thus there would be a question as to which measurement to use in responding to a query. One way to deal with this situation is to simply chose one of them arbitrarily for use in responding to a query, as was done in tested embodiment of the geometric model program. Alternately, as will be discussed next, the measurement having the lowest uncertainty estimate could be chosen and the others ignored. Alternatively, the two measurements could be combined using the relative uncertainties as weights in the combination process [1].

Measurements in the geometric model preferably reflect the spatial uncertainty associated with the method used to obtain them. For example, a measurement taken directly by a user might be considered more certain than the same measurement derived from images of the scene. One way of introducing an uncertainty estimate into the measurements is to employ a Gaussian uncertainty model where rather than a measurement being a particular value, it is provided to the geometric model program as a mean estimate for each coordinate and a covariance matrix for each that is indicative of the uncertainty of the coordinate mean [1]. The advantage of characterizing the measurements in the foregoing way is that it can be used to enhance certain optional procedures performed within the geometric model program that are designed to test the accuracy and possibly even revise the measurements provided to the program.

One class of error detection methods employs the concept of cycle-based constraints. Cycles can be best envisioned in reference Fig. 5. A cycle is a loop formed by connected entities frames. In Fig. 5, there are many such loops including CDEI, FGJK, FGK, GJK, BCDEFKH, and BCIEFKH, among others. In the environment these loops represent measurements from the origin of a first entity frame (which could be any one in the loop) to the next and so on until a measurement connects the next to last entity frame back to the origin of the first entity frame. The significance of a cycle is that the measurements around the loop

should return precisely to where they started, i.e. a "zero difference". If they do not then the previously provided uncertainty estimates could be used to adjust the measurements within the loop to obtain the desired zero difference. A conventional method for accomplishing this adjustment procedure is described in reference [2]. It is noted that this adjustment process could be repeated each time a new, updated measurement associated with a loop is received. Or alternately, the adjustment process could be repeated on a periodic basis to test the accuracy and revise the measurements in light of any new measurements that have been received. Further, it is noted that the adjustment procedure of reference [2] would produce only small changes, if any, for measurements with a high degree of certainty (such as those that were physically measured), whereas larger changes could be expected for those measurements having a low certainty.

Thus, referring to Fig. 6, the foregoing version of an error detection process, which could optionally be employed with the present geometric modeling program, would generally involve first identifying cycles of measurements within the measurement data (process action 600). Next, for each of the identified cycles, a difference is computed between a given location of an arbitrarily chosen first entity, as originally provided to the geometric modeling database, and the location of the chosen first entity's frame, as indicated by following the chain of measurements around the cycle (process action 602). Revised versions of one or more of the measurements making up the identified cycles are computed by simultaneously adjusting the measurements based on the previously-described uncertainty estimates associated with the measurements so as to make the location of the chosen first entity of each of the identified cycles as indicated by following the chain of measurements around the cycles to match the given location of those entities (process action 604). The reason for adjusting all the measurements of the identified cycles simultaneously is that a particular measurement may be part of more than one cycle. Simultaneously adjusting all the measurements ensures a "zero difference" is created for all the cycles, even those with shared measurements.

Another error detection procedure that could be implemented based on the aforementioned cycles involves detecting inconsistencies in the measurements.



Referring to Fig. 7, the first process action 700 of this alternate error detection procedure entails identifying cycles of measurements within the measurement data. Next, one of the identified cycles is selected (process action 702), and choosing one of the cycle's entity frames as the first frame (process action 704). The first entity

5 frame can be any one in the loop for which an actual location corresponding the origin of the frame has been previously specified. The measurements forming a selected cycle are then followed around the cycle from the chosen first entity frame to compute the location of the origin of the selected entity frame, while using the uncertainty estimates associated with each measurement to define an uncertainty

10 region around the computed origin location (process action 706). The uncertainty region essentially defines an area around the computed location. It is then determined if the specified location of the entity frame chosen as the first in the cycle falls within the computed uncertainty region, as indicated by process action 708. If so, then the measurements are considered to be accurate (process action 710). If,

15 however, the specified location falls outside the uncertainty region, then it is deemed that at least one of the measurements making up the cycle is incorrect (process action 712). It would not be known which measurement or measurements in the cycle are incorrect. However, knowing that at least one of them is in error, the geometric model program could be designed to disregard all the measurements that

20 are part of the cycle (process action 714). Further, the geometric model program could provide feedback to the program or programs that inputted the suspect measurements and request that new measurements be provided (process action 716). In either case, the error detection procedure is repeated for each remaining cycle (process action 718).

25 It is noted that the error detection procedures outlined in Figs. 6 and 7 could be combined as well. In this combined embodiment, the procedure would follow the actions outlined in Fig. 6. If it is determined that at least one of the measurements making up a cycle under consideration is inconsistent, then the measurements are

30 ignored and potentially replaced. However, if the computed location of the first entity frame of the cycle is not exactly the same as the specified location but falls within the aforementioned uncertainty region, then revised versions of the measurements making up the identified cycles would be computed.

Finally, the foregoing error detection procedures (Fig. 6 or Fig. 7 or the combined version) could be performed anytime a new measurement is provided to the geometric model database. Thus, for example, in the case of the procedure  
5 outlined in Fig. 7 where new measurements are requested when an error is found, the procedure would be performed again when the new measurements are received. Or, as mentioned previously, these procedures could be repeated on a periodic basis.

10 It was mentioned previously that an entity is represented in the geometric model as a coordinate frame and an extent. The extent of an entity will now be described. Real world entities will have some physical size. In addition, an physical object could have some service region, such as a field of view associated with a camera or display device. It is advantageous to augment the geometric model with  
15 these region descriptions, which are called extents. Thus, an inputting program would include in its description of an entity any extents associated with the entity. The geometric program would preferably treat each entity-extent combination which is related to the same physical item as separate entities with a measurement of zero between them. Thus, each entity has only one extent, but multiple entities may  
20 represent the same physical device in the model. By default in the preferred embodiment, if no extent is explicitly specified for an entity, a point extent is assumed. This point extent can be defined as being located at the origin of the entity's frame, or at a location having some prescribed geometric relationship to the origin of the entity's frame. It is noted that the description of the area in the  
25 environment associated with an extent is expressed in terms of the coordinate frame of the corresponding entity. The significance of this entity-extent approach will become apparent in the upcoming discussion of querying the geometric model program about geometric relationship in the environment. The extent of an entity can be expressed as having any planar geometric shape. However, in tested  
30 embodiments of the geometric model program the area associated with an extent was expressed as a polygon, (including degenerate cases such as a point when no extent is specified or a line segment such as in the case of a flat display screen which appears as a line from above)

## 2.0 Maintaining the Geometric Model

As described previously, the geometric model of the environment is constructed from three components input by outside programs. Namely, entities, extents associated with entities and measurements between entity frames.

However, the environment being modeled will typically change. For example, a new person could enter a room in the environment or someone could leave. Similarly, a new piece of I/O equipment could be added, or an old one replaced. Thus, entities will come and go, and the geometric model must be updated as to the current

entities existing in the environment, as well as to their current extents. In addition, entities can be expected to move about in the environment. For example, a person will typically move about a room. In addition, equipment can be relocated. Thus, it is necessary that the measurements between entity frames also be updated on an on-going basis to keep the geometric model current. The aforementioned entity and

measurement IDs are used in this updating process. In view of the need to keep the geometric model current an assumption is made that some mechanism is in place which causes the outside programs feeding the model program to input changes. As indicated previously, when an entity is created, an entity ID is assigned. Thus, any new entity introduced by an outside program would also be issued a unique entity ID.

Whenever, a outside program refers to an entity it does so by using the assigned entity ID. As a consequence, the outside programs must have the capability to retain these IDs. If an outside program indicates that an entity is no longer in the environment, the entity ID is deactivated and preferably not used again to prevent confusion. In a similar way, outside programs that input updated measurements

would do so by referring to the appropriate measurement ID. The same measurement ID can be retained for the updated version as the ID refers to the existence of geometric relationship between two entities not a specific instance of that relationship. However, if an entity associated with a measurement is eliminated from the geometric model, all the measurements corresponding to that entity should also be deleted, and preferably the measurement ID retired to prevent confusion.

### 3.0 Storing the Geometric Model

The geometric model database is preferably stored in a readily accessible memory, such as a RAM, while the geometric model program is running so as to facilitate updating the model and processing queries concerning the geographic relationships represented by the model. However, when the program is exited the model may be lost. Of course, the geometric model database could be rebuilt each time the program is executed. However, this requires the outside programs that feed entity, measurement and extent information into the geometric model program to supply this information each time. While a typical ubiquitous computing environment is dynamic in nature, many things do not change that often, such as the location of many I/O devices and sensors. Thus, there is some redundancy in re-building the model each time the geometric model program is executed that could be avoided. One way of avoiding this redundancy would be to store the relatively fixed or static portions of the model in a non-volatile memory and initialize the model using this information each time the geometric model program is executed. It is noted however, that since the entity IDs and measurement IDs associated with the static model data would be retained from one session to the next, any outside program that wishes to provide inputs or make queries would have to have the capability of permanently storing this information, or perhaps more practically, obtaining the IDs from a separate database maintained for that purpose.

In the event that some of the fixed portions of the geometric model change, or new fixed entities, etc., are added to the model, the initializing database could be updated accordingly so as to be as complete as possible the next time the geometric model program is executed.

### 4.0 Handling Queries Concerning the Relationships Between Entities.

The primary purpose of creating and maintaining the geometric model of the ubiquitous computing environment is to respond to queries about the geometric relationships between entities. While a query could be as simple as what extent is

associated with a particular entity, typically the requested information will be directed at the relationships between the various entities and/or their extents.

There are two fundamental types of queries about these relationships that the geometric model program will be called upon to answer. The first type is a query concerning the relative relationship between two entities. For example, the query may be a request to specify where entity B (e.g., a display screen) is in relation to entity A (e.g., a person). There may be a single measurement already existing between the frames of the entities in question. If so the answer to the query is straightforward. However, suppose there is no direct measurement between the between entities involved in the query. If at least one path of measurements exists between two entity frames, then a single geometric relationship can be derived between them. However, in such a case the geometric relationship must be derived from the multiple measurements making up the path. The first part of this process is to find the measurement path between the two entity frames in question. One way of doing this is to find a path having the fewest number of measurements between the query entities. This can be accomplished using a breadth-first search procedure. Essentially, a breadth-first search entails starting at the primary entity frame in the query (such as the frame associated with entity A in the example above) and identifying all the entity frames that have measurements between themselves and primary entity frame. The process continues by choosing each of the identified entity frames in turn and then finding and keeping track of all the entity frames having measurements between themselves and the identified entity frame. This stepwise process continues until one of the identified entity frames is associated with the other entity specified in the query. The path of measurements back to the primary entity frame is then identified. For example, referring to Fig. 5, suppose a query asked where entity L was in relation to entity J. First the entity frames connected to J would be identified, i.e., entity frame K and entity frame G in this case. Next the entity frames connected to the newly identified entity frames would be found. In this case, entity frame K is connected to entity frames F, G and H, while entity frame G is connected to entity frames F, K and L. Since entity frame L has been identified the search is over and the measurement path JGL is identified. This should be the path having the smallest number of measurements. It is noted that if two paths have the

same number of measurements (i.e., a tie), either could be chosen arbitrarily, or some selection criteria such as the collective uncertainty of the path could be employed to make the choice. The next phase of the response to the first type of query involving the geometric relationship between two entities is to compute a  
5 single measurement describing the relationship and output it to the querying program. As mentioned previously, if there is a single measurement existing between the frames of the query entities, it can be used directly to respond to the query. However, when a path having multiple measurements is identified between the frames of the query entities, the measurements must be combined or "fused" to  
10 yield a response. Any conventional method of accomplish this fusion can be employed, such as for example the process described in reference [1].

The foregoing process for handling queries concerning the relative geometric relationship between two entities of the database is summarized in the flow diagram  
15 of Fig. 8. The first action 800 of the process involves waiting for queries concerning the relative geometric relationship between two entities. Periodically, it is determined whether such a query was received as indicated in process action 802. If no query was received, the waiting and checking actions 800 and 802 are continued. If, however, such a query was received, then it is ascertained whether or not a direct  
20 measurement exists in the database between the two entities that are the subject of the query (process action 804). If so, then the requested measurement is provided to the source of the query (process action 806). Whenever there is no direct measurement available, a breadth-first search is employed to find a measurement path between the two entities involved in the query that has the fewest number of  
25 measurement links (process action 808). It is next determined in process action 810 whether a path was found at all. If no path was found, then the source of the query is informed that the requested information cannot be provided (process action 812). However, if a path was found, then the requested measurement is computed using the measurements in the discovered path (process action 814), and the requested  
30 measurement is provided to the source of the query (process action 816). The monitoring is continued and foregoing procedure repeated every time a new query concerning the relative geometric relationship between two entities is received.

The second type of query concerns a request to find an entity or set of entities whose extents have a particular geometric relationship to a given entity. The first phase of this process is to define the relationship between the given entity frame and each of the other entity frames in terms of the given entity's coordinate frame. This is accomplished just as it was in responding to the first type of query, with the exception that it is repeated to find the relationship between the given entity frame and every other entity frame, not just for one other. There may be cases where the relative geometric relationship between the frame of the given entity and the frame of one of the other entities involved in the query could not be determined due to a lack of the measurement path needed to compute the relationship. This circumstance is noted and reported to the query source in the manner described below.

The next phase in this type of query could generally be characterized as a region intersection problem. Essentially, some region associated with a given entity frame is specified. This region could be a newly defined region, or it might be the aforementioned extent of the entity associated with the frame. A newly defined region could be any desired planar shape, however, for convenience the following description will assume the newly defined region (or one corresponding to an entity's extent) is a polygon as was used in tested embodiments of the geometric model program. As an example of where a newly defined region comes into play, suppose a query asks for all the entities which have extents within some prescribed distance of a given entity. The geometric relationships between the given entity and all others in the environment are computed, as described above. Then, a polygonal region surrounding the given entity would be defined based on the prescribed distance and in terms of the given entity's coordinate frame. The extents associated with all the other entities would also be transformed using the computed relationships into the given entity's coordinate frame. A standard polygon intersection technique (or similar procedure if the region is characterized by a planar shape other than a polygon) would then be employed to determine if extents associated with the other entities intersect the defined region. Those entities whose extents are discovered to intersect the region would be reported to the program making the query.

An example of a query where the extent of a given entity is involved would be as follows. Suppose a query asked what entities are at least partially in the field of view of a camera, where the camera is an entity in the geometric model and the field of view is its extent. First, the respective geometric relationships between the entity  
5 frame representing the camera and the frames of all the other entities in the model are computed in terms of the camera-entity's coordinate frame. The extents defining the other entities are then transformed into the camera-entity's coordinate frame. A standard polygon intersection technique (or similar procedure if the extents are characterized by a planar shape other than a polygon) would then be employed to  
10 determine if any portion of the other entities' extents overlap the extent of the camera-entity representing its field of view. Those entities having extents that are discovered to overlap would be reported as being within the camera's field of view to the program making the query.

15 As a further example, consider a query that requests if a person can clearly see a display screen. One way to handle this query would be to define a triangular region in terms of the person-entity's coordinate frame that has one vertex corresponding to a point midway between the person's eyes and its other two vertices corresponding to points at opposite sides of the display screen. This could  
20 be done by first querying for the geometric relationship between the person and the display, and utilizing information about the size of the display to determine where the edges should be located. The process would proceed as described above by computing the relationships between the frames of each entity in the environment and the frame of the person-entity. The extents which define the other entities' are  
25 transformed using these computed relationships into the person-entity's coordinate frame. A polygon intersection technique (or similar procedure if the defined region and extents are characterized by a planar shape other than a polygon) would then be used to determine if any portion of the other entities' extents overlap the newly defined region. The entities which intersect the original triangular region would be  
30 reported back to the querying program. Since extents in the model may represent non-physical things such as regions of service (which would not obscure view of a screen), it could be left up to the querying program to determine which of the intersecting extents actually represent things which obscure vision. For example, an



entity which represents a field of view of a camera would not obscure a person's sight of a display.

5       The foregoing process for handling queries concerning a request to find an  
entity or set of entities whose extents have a particular geometric relationship to a  
prescribed region or extent associated with a given entity is summarized in the flow  
diagram of Fig. 9. The first action 900 of the process involves waiting for queries  
concerning the aforementioned request. Periodically, it is determined whether such  
a query was received as indicated in process action 902. If no query was received,  
10   the waiting and checking actions 900 and 902 are continued. If, however, such a  
query was received, then the relative geometric relationship is computed between  
the frame of the given entity and the frames of all other entities connected to it by a  
chain of measurements (process action 904). Next, the coordinates of the extents  
associated with these other entities are transformed into the coordinate frame of the  
15   given entity using the respective relative geometric relationships computed  
previously between the given entity and the other entities (process action 906). A  
region intersection process is then employed to determine if the extents associated  
with the other entities involved in the query intersect the prescribed region or extent  
associated with the given entity (process action 908). Finally, in process action 910  
20   the intersection information (i.e. which entities along with optionally the region of  
intersection of each extent) is provided to the requesting source. The monitoring is  
continued and foregoing procedure repeated every time a new query of the  
aforementioned type is received.

25       Another interesting aspect of the last example is that even if there are no  
overlapping extents, this does not mean that the person is actually facing toward the  
display screen. The purpose for the query may be that the querying program wants  
to display something intended for the person to see. This is where the  
aforementioned rotational coordinates used to indicate the "heading" of an entity  
30   could come into play. For instance, if the rotation component associated with the  
person indicates that the display screen would be in his or her field of view, then this  
would be reported. If not, then it could be reported to the querying program that the  
person could not see the display screen. The same procedure could be performed

in the context of the display screen to ensure that it is oriented such that the person can see it.

It is noted that a query could be of a one-time or "one-shot" nature, or may be a standing query. For a one-time query, the querying program would request the desired geometric information and receive a one-time response. However, a standing query would be one predicated on some event, and every time this event occurred, a response to the query would be provided. For example, the previously discussed query concerning whether a person could clearly see a display screen might be requested to be responded to every time the person of interest is added to the geometric model of the environment (e.g., enters a room). It is also noted that because the environment is dynamic the response to such a query may have to be re-computed each time it is responded to, rather than relying on the previous response.

### References

[1] R. Smith, P. Cheeseman. "On the Representation and Estimation of Spatial Uncertainty". International Journal of Robotics Research, Vol. 5, No. 4, pp. 56-67, Winter 1986.

[2] P. Newman. "On The Structure and Solution of the Simultaneous Localisation and Map Building Problem". Ph.D Thesis, March 1999.

**CLAIMS**

What is claimed is:

- 5           1.     A computer-implemented process for providing a geometric model database for use in a ubiquitous computing environment to respond to queries about the environment's geometric state, characterized by using a computer to perform the following process actions:
- accepting information about the geometric state of the environment;
- 10           building a geometric model database of the environment based on an initial input of said information;
- maintaining the geometric model database by modifying it based on the input of updated information about the geometric state of the environment; and
- responding to queries concerning the geometric relationships between
- 15           entities in the environment using the geometric model database.
2.     The process of Claim 1, wherein the process action of accepting information about the geometric state of the environment, is characterized by the actions of:
- 20           inputting identifying information from an external source concerning an object existing in the environment, referred to as an entity, which is to be included in the geometric model database, said information characterized by the entity's extent which is one of (i) the physical size of the entity, or (ii) the service region of the entity; and
- 25           inputting measurements, each of which defines the entity's relationship to one other entity in the geometric model database.
3.     The process of Claim 2, wherein the entity represents a camera and the camera's extent corresponds to a service region constituting a field of view of the
- 30           camera.
4.     The process of Claim 1, wherein the process action of building the geometric model database, is characterized by the actions of:

establishing a set of entities that are of interest in the environment;  
representing each entity by a coordinate frame and an extent, wherein  
said extent defines one of (i) the physical size of the entity, or (ii) the service region  
of the entity; and

5 characterizing the location of each entity in the environment relative to  
other entities using a measurement defining the entity's relationship to at least one of  
said other entities.

10 5. The process of Claim 4, wherein the process action of establishing a  
set of entities, is characterized by the actions of:

accepting identifying information from an external source concerning  
an object existing in the environment, referred to as an entity, which is to be included  
in the geometric model database, said information characterized by the entity's  
extent assigning a unique entity identifier to each entity which is then used by the  
15 geometric model database and the external source in referring to the entity; and  
making the entity identifiers available to the external source.

20 6. The process of Claim 5, wherein an external source provides more  
than one extent for an entity, and wherein the process action of assigning a unique  
entity identifier to each entity, is characterized by the actions of:

assigning a separate identifier to each entity-extent combination; and  
setting the measurement between entity-extent combinations  
associated with the same entity to zero.

25 7. The process of Claim 4, wherein the process action of representing  
each entity by a coordinate frame and an extent, is characterized by a process action  
of representing each entity by a coordinate frame having a fixed geometric  
relationship to the physical object associated with the entity.

30 8. The process of Claim 4, wherein the process action of representing  
each entity by a coordinate frame and an extent, is characterized by a process action  
of characterizing an entity's extent as a polygonal region within the environment

defined in terms of the entity's coordinate frame whenever the external source provides information as to the shape of the entity's extent.

9. The process of Claim 4, wherein the process action of representing  
5 each entity by a coordinate frame and an extent, is characterized by a process action of characterizing an entity's extent as a line segment within the environment defined in terms of the entity's coordinate frame whenever the external source provides information indicating the entity's extent to be such a line segment.

10 10. The process of Claim 4, wherein the process action of representing each entity by a coordinate frame and an extent, is characterized by a process action of characterizing an entity's extent as a point coincident with the origin of the entity's coordinate frame whenever the external source fails to provide information defining a size for the entity's extent.

15 11. The process of Claim 4, wherein the process action of representing each entity by a coordinate frame and an extent, is characterized by a process action of characterizing an entity's extent as a point having a prescribed geometric relationship to the origin of the entity's coordinate frame.

20 12. The process of Claim 4, wherein the process action of characterizing the location of each entity in the environment relative to other entities using a measurement defining the entity's relationship to one of said other entities, is characterized by an action of using a measurement specifying the position and  
25 orientation of each other entity's coordinate frame origin in terms of the coordinate frame of the entity under consideration.

30 13. The process of Claim 4, wherein the process action of characterizing the location of each entity in the environment relative to other entities using a measurement defining the entity's relationship to at least one of said other entities, is characterized by the actions of:

assigning a unique measurement identifier to each measurement which is then used by the geometric model database and the external source in referring to the measurement defining the entity's relationship to another entity; and

making the measurement identifiers available to the external source.

5

14. The process of Claim 12, wherein the process action of using a measurement specifying the position and orientation of each other entity's coordinate frame origin in terms of the coordinate frame of the entity under consideration, is characterized by an action of assigning a spatial uncertainty estimate to the measurement which is indicative of the accuracy of the method used to obtain the measurement.

15. The process of Claim 14, wherein each measurement is provided to the geometric model database by an external source, and wherein more than one measurement defining an entity's relationship to another entity may be provided by separate external sources, and wherein the process action of characterizing the location of each entity in the environment relative to other entities using a measurement, is characterized by an action of, whenever more than one measurement defining an entity's relationship to another entity is received, using only the measurement having the lower uncertainty.

16. The process of Claim 14, wherein each measurement is provided to the geometric model database by an external source, and wherein more than one measurement defining an entity's relationship to another entity may be provided by separate external sources, and wherein the process action of characterizing the location of each entity in the environment relative to other entities using a measurement, is characterized by an action of, whenever more than one measurement defining an entity's relationship to another entity is received, arbitrarily choosing one of the measurements for use in characterizing the locations.

30

17. The process of Claim 14, wherein each measurement is provided to the geometric model database by an external source, and wherein more than one measurement defining an entity's relationship to another entity may be provided by

separate external sources, and wherein the process action of characterizing the location of each entity in the environment relative to other entities using a measurement, is characterized by an action of, whenever more than one measurement defining an entity's relationship to another entity is received, combining said measurements using their relative uncertainties as weights.

18. The process of Claim 4, wherein the process action of characterizing the location of each entity in the environment relative to other entities using a measurement defining the entity's relationship to one of said other entities, is characterized by an action of revising the measurements, said revising action characterized by the actions of:

inputting a spatial uncertainty estimate associated with each measurement which is indicative of the accuracy of the method used to obtain the measurement;

identifying cycles of measurements among the measurements, wherein a cycle of measurements is defined as a string of measurements starting at the origin of a first entity frame in the cycle and following measurements from one entity to the next until reaching a last measurement in the cycle representing the relationship between the coordinate frame of a next to last entity of the cycle and the origin of said first entity frame; and

for each cycle identified, computing the difference between a given location of said first entity frame's origin and the location of that origin as indicated by following the chain of measurements making up the cycle;

computing revised measurements for the identified cycles by simultaneously adjusting the measurements based on their associated uncertainty estimates so as to make the difference in the given location of said first entity frame's origin in each of the identified cycles match the location of that origin as indicated by following the chain of measurements making up the cycle

19. The process of Claim 18, further characterized by a process action of repeating the process actions of inputting spatial uncertainty estimates, identifying cycles of measurements, computing the difference between a given location of said first entity frame's origin and the location of that origin as indicated by following the

chain of measurements making up the cycle for each cycle identified, and computing revised measurements, whenever new measurements are provided.

20. The process of Claim 18, further characterized by a process action of  
5 repeating the process actions of inputting spatial uncertainty estimates, identifying cycles of measurements, computing the difference between a given location of said first entity frame's origin and the location of that origin as indicated by following the chain of measurements making up the cycle for each cycle identified, and computing revised measurements, on a periodic basis.

10 21. The process of Claim 4, wherein the process action of characterizing the location of each entity in the environment relative to other entities using a measurement defining the entity's relationship to at least one of said other entities, is characterized by an action of detecting errors in the measurements, said error  
15 detecting action characterized by the actions of:

(a) inputting a spatial uncertainty estimate associated with the measurement which is indicative of the accuracy of the method used to obtain the measurement;

(b) identifying cycles of measurements among the measurements,  
20 wherein a cycle of measurements is defined as a string of measurements starting at the origin of a first entity frame in the cycle and following measurements from one entity to the next until reaching a last measurement in the cycle representing the relationship between the coordinate frame of a next to last entity of the cycle and the origin of said first entity frame; and

25 (c) for each cycle identified,  
computing the location of said first entity frame's origin as indicated by following the chain of measurements making up the cycle, along with computing an uncertainty region around the computed location of the origin based on a combination of the uncertainty estimates associated with each measurement in the  
30 cycle,

determining if a given location of said first entity frame's origin is within the computed uncertainty region;



whenever the given location falls outside the uncertainty region,  
declaring that at least one of the measurements in the cycle is incorrect, and  
whenever it is declared that one of the measurements in the  
cycle is incorrect, disregarding these measurements and requesting that  
5 replacement measurements be provided.

22. The process of Claim 21, further characterized by a process action of  
repeating process action (c) whenever replacement measurements are provided.

10 23. The process of Claim 21, further characterized by a process action of  
repeating process action (c) periodically.

24. The process of Claim 4, wherein the process action of characterizing  
the location of each entity in the environment relative to other entities using a  
15 measurement defining the entity's relationship to one of said other entities, is  
characterized by an action of revising the measurements, said revising action  
characterized by the actions of:

(a) inputting a spatial uncertainty estimate associated with each  
measurement which is indicative of the accuracy of the method used to obtain the  
20 measurement;

(b) identifying cycles of measurements among the measurements,  
wherein a cycle of measurements is defined as a string of measurements starting at  
the origin of a first entity frame in the cycle and following measurements from one  
entity to the next until reaching a last measurement in the cycle representing the  
25 relationship between the coordinate frame of a next to last entity of the cycle and the  
origin of said first entity frame;

(c) for each cycle identified,  
computing the location of said first entity frame's origin as  
indicated by following the chain of measurements making up the cycle, along with  
30 computing an uncertainty region around the computed location of the origin based on  
a combination of the uncertainty estimates associated with each measurement in the  
cycle,

determining if a given location of said first entity frame's origin is within the computed uncertainty region,

whenever the given location falls outside the uncertainty region, declaring that at least one of the measurements in the cycle is incorrect, and

5 whenever it is declared that one of the measurements in the cycle is incorrect, disregarding these measurements and requesting that replacement measurements be provided, and

(d) computing revised measurements for those identified cycles in which the given location of the origin is not the same as its computed location but in  
10 which the given location falls within the uncertainty region by simultaneously adjusting the measurements based on their associated uncertainty estimates so as to make the difference in the given location of said first entity frame's origin in each of the identified cycles match the location of that origin as indicated by following the chain of measurements making up the cycle.

15

25. The process of Claim 24, further characterized by a process action of repeating process actions (a) through (d) whenever new measurements are provided.

20 26. The process of Claim 24, further characterized by a process action of repeating process actions (a) through (d) periodically.

27. The process of Claim 4, wherein the process action of responding to queries concerning the geometric relationships between entities in the environment,  
25 is characterized by an action of, upon receiving a request from an external source to identify the extent of a particular entity, providing the extent information to the external source.

28. The process of Claim 4, wherein the process action of responding to  
30 queries concerning the geometric relationships between entities in the environment, is characterized by the actions of:

waiting for incoming queries from external sources for requests concerning the relative geometric relationship between two entities;

whenever a request concerning the relative geometric relationship between two entities is received, determining if a direct measurement exists between the two entities involved in the request;

whenever said direct measurement exists, providing information  
5 concerning the measurement to the external source making the request.

29. The process of Claim 4, wherein the process action of responding to queries concerning the geometric relationships between entities in the environment, is characterized by the actions of:

10 waiting for incoming queries from external sources for requests concerning the relative geometric relationship between two entities;

whenever a request concerning the relative geometric relationship between two entities is received, determining if a direct measurement exists between the two entities involved in the request;

15 whenever said direct measurement does not exist, employing a breadth-first search to find a measurement path between the two entities involved in the request that has the fewest number of measurement links, wherein a measurement path is a chain of measurements from a first of the two entities involved in the request, through at least one intermediate entity, to the other entity  
20 involved in the request;

computing the requested measurement information using the measurements in said measurement path, if one was found; and

providing the computed measurement information to the external source making the request.

25

30. The process of Claim 29, wherein the process action of responding to queries concerning the geometric relationships between entities in the environment, further is characterized by, whenever as a result of employing the breadth-first search more than one measurement path is discovered having the same fewest  
30 number of measurement links, randomly choosing one of the discovered measurement path for use in computing the requested measurement information.

31. The process of Claim 29, wherein the process action of using a measurement specifying the position and orientation of each other entity's coordinate frame origin in terms of the coordinate frame of the entity under consideration, is characterized by an action of assigning a spatial uncertainty estimate to the measurement which is indicative of the accuracy of the method used to obtain the measurement, and wherein the process action of responding to queries concerning the geometric relationships between entities in the environment, further is characterized by, whenever as a result of employing the breadth-first search more than one measurement path is discovered having the same fewest number of measurement links, choosing the discovered measurement path exhibiting a lowest combined uncertainty for use in computing the requested measurement information.

32. The process of Claim 4, wherein the process action of responding to queries concerning the geometric relationships between entities in the environment, is characterized by the actions of:

inputting incoming queries from external sources for requests to find entities whose extents have a particular geometric relationship to a prescribed region or extent associated with a specified entity

ascertaining the relative geometric relationship between the frame origin of the specified entity and the frame origins of other entities

transforming the coordinates of the extents associated with the other entities into the coordinate frame of the specified entity using the respective relative geometric relationships between the frame origin of the specified entity and the frame origins of said other entities;

employing a region intersection procedure to determine if the extents associated with said other entities intersect the prescribed region or extent associated with the specified entity; and

providing information to the requesting source as to whether the extents of any of said other entities intersect the prescribed region or extent of the specified entity, and if so which of the other entities' extents intersect.

33. The process of Claim 4, wherein the prescribed region or extent associated with the specified entity, as well as the extents associated with said other

entities, are characterized by polygonal areas, or degenerated version thereof constituting a line segment or point, and wherein the region intersection procedure is a polygon intersection procedure.

5           34.    The process of Claim 1, wherein the process action of responding to queries concerning the geometric relationships between entities in the environment, is characterized by an action of, upon receiving a standing request from an external source, responding to the request each time a prescribed event occurs.

10           35.    A system for providing a geometric model database for use in a ubiquitous computing environment to respond to queries about the environment's geometric state, characterized by:

at least one general purpose computing device; and

a computer program characterized by program modules executable by

15   the computing device or devices, wherein the computing device or devices are directed by the program modules of the computer program to,

input information about the geometric state of the environment from at least one external source,

establish a set of entities that represent objects in the

20   environment based on an initial input of said information,

represent each entity by a coordinate frame and an extent, wherein said extent is based on an initial input of said information,

characterize the location of each entity in the environment relative to other entities using a measurement defining the entity's relationship to at

25   least one of said other entities.

36.    The system of Claim 35, further characterized by:

a program module for storing as initializing data in a non-volatile initializing database, information concerning the entities, their extents, and the

30   measurements between entities contained within the geometric model database; and wherein,

the program module for inputting information about the geometric state of the environment, is characterized by an action of inputting the stored initializing

data from the non-volatile database at the start of said process for providing a geometric model database.

37. The system of Claim 36, wherein the program module for storing  
5 initializing data, is characterized by a sub-module for storing only information concerning entities, extents, and measurements that is anticipated not to change substantially over time.

38. The system of Claim 37, wherein the program module for inputting  
10 information about the geometric state of the environment, is characterized by a sub-module for inputting update information characterizing a current geometric state of the environment.

39. The system of Claim 38, wherein the program module for storing  
15 initializing data, is characterized by a sub-module for storing information concerning the entities, their extents, and the measurements representative of the most current geometric state of the environment.

40. The system of Claim 36, wherein the program module for establishing  
20 a set of entities is characterized by a sub-module for assigning a unique entity identifier to each entity entered into the geometric model database, which is then used by the geometric model database and external sources in referring to the entity, and wherein the program module for characterizing the location of each entity in the environment relative to other entities using a measurement is characterized by a  
25 sub-module for assigning a unique measurement identifier to each measurement entered into the geometric model database, which is then used by the geometric model database and the external sources in referring to the measurement.

41. The system of Claim 40, wherein the program module for storing  
30 initializing data, further is characterized by sub-modules for:

storing the entity and measurement identifiers assigned to the entities and measurements characterized by the initializing data in a non-volatile initializing database; and

making the entity and measurement identifiers available to the external sources.

42. A computer-readable medium having computer-executable instructions  
5 for providing a geometric model database for use in a ubiquitous computing environment to respond to queries about the environment's geometric state, said computer-executable instructions characterized by:

inputting information about the geometric state of the environment from at least one external source,

10 building a geometric model database of the environment based on an initial input of said information, and

maintaining the geometric model database by modifying it based on the input of updated information about the geometric state of the environment.

15 43. The computer-readable medium of Claim 42, wherein the instruction for building the geometric model database, is characterized by sub-modules for:

establishing a set of entities representing objects in the environment;

representing each entity by a coordinate frame and an extent; and

characterizing the location of each entity in the environment relative to

20 other entities using a measurement defining the entity's relationship to one of said other entities.

44. The computer-readable medium of Claim 43, wherein the instruction for  
inputting information about the geometric state of the environment, is characterized  
25 by a sub-module for inputting update information characterizing a current geometric state of the environment.

45. The computer-readable medium of Claim 44, wherein the instruction for  
maintaining the geometric model database, is characterized by a sub-module for  
30 updating the geometric model database on an on-going basis, using the inputted update information characterizing a current geometric state of the environment, to ensure to the best degree possible given the update information, that only entities currently existing in the environment and their associated current extents are

included in the database, and that measurements between the current entities are representative of the current geometric relationships between the current entities.

46. The computer-readable medium of Claim 45, wherein the sub-module  
5 for establishing a set of entities, is characterized by sub-modules for:

assigning a unique entity identifier to each entity entered into the  
geometric model database, which is then used by the geometric model database and  
external sources in referring to the entity; and  
making the entity identifiers available to the external sources.

10

47. The computer-readable medium of Claim 46, wherein the sub-module  
for establishing a set of entities, further is characterized by a sub-module for  
deactivating existing entity identifiers associated with entities that are indicated in  
said update information as no longer being in the environment.

15

48. The computer-readable medium of Claim 47, wherein the sub-module  
for characterizing the location of each entity in the environment relative to other  
entities using a measurement, is characterized by sub-modules for:

assigning a unique measurement identifier to each measurement  
20 entered into the geometric model database, which is then used by the geometric  
model database and external sources in referring to the measurement; and  
making the measurement identifiers available to the external sources.

49. The computer-readable medium of Claim 48, wherein the sub-module  
25 for deactivating existing entity identifiers associated with entities that are indicated in  
said update information as no longer being in the environment, is characterized by  
sub-modules for:

deleting all measurements associated with a deactivated entity from  
the geometric model database; and  
30 retiring the measurement identifier assigned to any measurement that  
is deleted for being associated with a deactivated entity.




50. The computer-readable medium of Claim 43, wherein the sub-module for characterizing the location of each entity in the environment relative to other entities using a measurement, is characterized by sub-modules for:

- assigning a unique measurement identifier to each measurement
- 5 entered into the geometric model database, which is then used by the geometric model database and external sources in referring to the measurement; and
- making the measurement identifiers available to the external sources.

51. The computer-readable medium of Claim 50, wherein the sub-module  
10 for characterizing the location of each entity in the environment relative to other entities using a measurement, further is characterized by sub-modules for:

- whenever a new current measurement is provided in said inputted update information, using it to replace the corresponding measurement already existing in the geometric model database; and
- 15 assigning the measurement identifier associated with the existing measurement to the new current measurement.

FIG. 1






FIG. 2




FIG. 3




FIG. 2A




FIG. 4




FIG. 5





FIG. 6








FIG. 8




FIG. 9